August 25, 2026
Our 97th Year

Ship To:
120 S. Hospital Rd.
Sandersville, GA 31082
Attn: Greg Taylor Phone:
(478) 357-0009
Email: gtaylor@sandersvillega.org

Bill To:
P.O. Box 71
Sandersville, GA 31082

Altec Quotation Number:

Account Manager: Daniel Keith
Technical Sales Rep: Cameron D Jones

Item	Description	Qty	Price
	Unit		

1. Altec Model AT41M Articulating Telescopic Aerial Device with a fiberglass upper boom and fiberglass insulator in the articulating arm and proportional joystick upper controls. Built in accordance to ALTEC's standard specifications and to include the following features: 1

   A. Ground to Bottom of Platform Height: 40.8 feet at 7.3 feet from centerline of rotation (12.45 m at 2.21 m)
   B. Working Height: 45.8 feet (13.96 m)
   C. Maximum reach to edge of platform with Upper Boom Non- overcenter: 30.1 feet (at 17.3 feet platform height)
   D. Upper boom extension: 110 inches
   E. Continuous rotation
   F. Articulating Arm: Articulation is from -3 to 82 degrees. Insulator provides 19 inches of isolation.
   G. Compensation System: By raising the articulating arm only, the telescopic boom maintains its relative angle in relation to the ground. The work position is achieved through a single function operation.
   H. Upper Boom: Articulation is from -25 to 85 degrees. The fiberglass section provides a minimum of 10.9 inches of isolation in the upper boom (when retracted and 42.3 inches when extended).
   I. Platform leveling is achieved by a hydraulic master-slave leveling system. This lifetime system is very low maintenance.
   J. The dielectrically tested, insulating upper control system includes the following boom tip components that can provide an additional layer of secondary electrical contact protection.
   Control Handle: A single handle controller incorporating high electrical resistance components that is dielectrically tested to 40 kV AC with no more than 400 microampers of leakage. The control handle is green in color to differentiate it from other non-tested controllers. The handle also includes an interlock guard that reduces the potential for inadvertent boom operation.
   Auxiliary Control Covers: Non-tested blue silicon covers for auxiliary controls.

Item	Description	Qty	Price
71.	Standard Altec Warranty: One (1) year parts warranty, one (1) year labor warranty, ninety (90) days warranty for travel charges, limited lifetime structural warranty	1	

Miscellaneous

72.	Non-CARB Registered State	1	

Unit / Body / Chassis	$206,500.0
Upfits	$21,346.00
Total	$227,846.0

Altec Industries, Inc.